

KZP-G165 DIESEL GENERATOR SET / 50Hz



Emergency Standby Power (ESP)

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Prime Power

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3)

OUTPUT RATINGS

50 Hz / 400V

Standby Power	165 kVA
	132 KW
Prime Power	150 kVA
	120 KW

ENGINE (ESP -STAND-BY)

Manufacturer	PERKINS
Origin	UK
Model	1006TAG2
No of Cylinder / Configuration	6 / IN LINE
Displacement (lt)	6
Bore / Stroke (mm)	100 / 127
Cycle	4
Compression Ratio	17.0 :1
Aspiration	Turbo
Governor Type	Electronic
Cooling System	Water
Coolant Capacity (lt)	37,2
Lubrication Oil Capacity (lt)	19
Injection	Direct
Speed / Frequency	1500 / 50 Hz
Engine Gross Power (kWm)	133,2
Fuel Consumption (lt/h)	100% 41
	50% 20

ALTERNATOR

Manufacturer	GENTECH
Origin	TURKEY
Model	GNT-165
No of Phase	3
Power Factor	cos 0,8
Number of Bearing	SINGLE
No of Poles	4
No of Leads	12
Voltage Regulation (Steady State)	± %1
Insulation Class	H
Degree of Protection	IP 21/23
Excitation System	AVR, Brushless
Connection Type	STAR
Total Harmonic Content (No Load)	< %2
Frequency (Hz)	50
Voltage Output (VAC)	230 / 400
Efficiency (%)	%91,7

Sound Proof Canopy



Special design for minimizing acoustic level
Galvanised steel construction further protected by polyester powdercoat paint
Black finish stainless steel locks and hinges
Control panel viewing window in a lockable access door
Emergency stop push button (red) mounted on enclosure exterior
Lifting, drag and jacking points on base frame
Radiato fill via removable, flush mounted rain cap fitted with compression seal
Acoustic insulation with moisture-repellent and non-flammable material

Dimensions	WxLxH	Weight	Fuel Tank	Noise
	mm	kg	lt	db(A)
CANOPIED	1100x3350x1910	1995	400	
OPEN SET	1095x2300x1600	1535	400	

CONTROL UNIT

STANDART: Datakom309

OPTIONAL: Deepsea



KZ POWER reserves the right to amend details and specifications without notice.
Images for illustration purposes only. Generating set may include optional accessories.



KZ ENERJİ ÇÖZÜMLERİ ve DİŞ TİC. LTD. STİ.
Mimar Sinan Mah. Bosna Caddesi No : 1/6
Cekmekoy / İstanbul / Turkey
T : +90 216 527 29 19
M : +90 532 255 76 77
F : +90 216 641 96 47
www.kzpower.com
info@kzpower.com